



Anleitung Car Cradle USB-C Connector



(1)



(2)




(3)

Zunächst muss das iPad in das aiShell™ eingesetzt werden. Um den USB-C-Stecker einzusetzen, muss dieser mit der Nut an der Vorderseite des aiShell™ ausgerichtet werden (1). Der Stecker kann anschließend fest in das Gehäuse gedrückt werden (2).

Vor der Entnahme des iPad aus dem aiShell™, muss der Connector entfernt werden. Hierzu die beiden Flügel am Connector nach unten drücken und den Connector auf einer Seite aus dem Gehäuse ziehen (3).


Wichtig:

Der USB-C Car Cradle Connector ist **nur** für die Verwendung mit einem aiShell™ vorgesehen. Um das aiShell™ zu öffnen, **muss** der Connector zuerst entfernt werden. Weitere Informationen und Hilfestellungen finden Sie hier.





Manual Car Cradle USB-C Connector



(1)



(2)



(3)

First, the iPad needs to be inserted into the aiShell™. To insert the USB-C connector align it with the notch on the front of the aiShell™ (1). The connector can then be pressed firmly into the case (2).

Before removing the iPad from the aiShell™, the connector has to be removed. To do this, press the two wings on the connector down and pull the connector out of the housing on one side (3).

Important:

The Car Cradle USB-C Connector is intended for use with the aiShell™ **only**. To open the aiShell™, the connector **must** first be removed. More Information can be found [here](#).



Electrical appliances must not be disposed of with household waste. According to EU Directive 2012/19/EU, power tools must be collected separately and recycled in an environmentally friendly manner.



CE conformity mark
Berlin 2023

Andres Industries AG
Weißenseer Weg 37
13055 Berlin
www.andres-industries.de