BN ESSENTIAL Metered
Messung pro Phase
Eingang: 16A/400V | 11kW
Ausgang: 24xC13 0° Kaltgerätekabel
6xC19 90° Kaltgerätesteckdose
6xCEE7/3 35° Schuko-Steckdose rotierbar
aufgeteilt auf drei Phasen
Zuleitung: 3,0m | 2,5mm²
mit CEE 16A Stecker, rot
Integrierte Funktion zur Messung von Strom, Spannung, Wirk-, Blind-, Scheinleistung, Wirkenergie, Frequenz und Leistungsfaktor
Im Betrieb tauschbarer Controller
Integrierter Webserver mit Webinterface
2x 1Gbit/s Ethernetanschluss
1x USB-A Anschluss
2x Schnittstelle für Sensoren
2,8" TFT Farbdisplay
inkl. Halterwinkel
mit BACHMANN Logo
Verpackt im Karton

BN ESSENTIAL Metered
Metering per Phase
Input: 16A/400V | 11kW
Output: 24xC13 0° IEC Socket
6xC19 90° IEC Socket
6xCEE7/3 35° Socket
split into three phases
Supply cable: 3,0m | 2,5mm²
with CEE 16A plug, red
Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
Not-swappable controller
Integrated web server with web interface
2x 1Gbit/s Ethernet connection
1x USB-A port
2x Interface for sensors
2,8" TFT color display
incl. mounting brackets
with BACHMANN logo
Packed in carton