



<p>BN ESSENTIAL Metered Messung pro Phase Eingang: 16A/230V 3,6kW Ausgang: 4xC13 0° Kaltgerätedose 2xC19 90° Kaltgerätedose Einspeisung: mit C20 Einbaustecker Integrierte Funktion zur Messung von Strom, Spannung, Blind-, Schein-, Wirkleistung, Wirkenergie, Frequenz und Leistungsfaktor Im Betrieb tauschbarer Controller Integrierter Webserver mit Webinterface 2x 1Gbit/s Ethernetanschluss 1x USB-A Anschluss 2x Schnittstelle für Sensoren 2,0" TFT Farbdisplay inkl. Haltewinkel mit BACHMANN Logo Verpackt im Karton</p>	<p>BN ESSENTIAL Metered Metering per Phase Input: 16A/230V 3,6kW Output: 4xC13 0° IEC Socket 2xC19 90° IEC Socket Power Supply: with C20 Built-In Connector Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor Hot-swappable controller Integrated web server with web interface 2x 1Gbit/s Ethernet connection 1x USB-A port 2x Interface for sensors 2.0" TFT color display incl. mounting brackets with BACHMANN logo Packed in carton</p>
---	---

Werkstoff / Material	Gewicht / 0 kg	Microfläche / Surface
Bezeichnung / Title	BN ESSENTIAL Metered	
Dratum / Name		
in 01-2020	01	
Druck / Draw-No		
Art-Nr.	BM0024221	1 1
Format / Draw-Size	A1	1